



Fortus 900mc

Designed and built for size, throughput, precision and repeatability.

The Fortus 900mc™, the most precise and largest of the Performance family, is designed to handle your most demanding digital manufacturing needs. With the largest build size of any Fortus® system and significant upgrades in its mechanical, electromechanical and electrical systems, the Fortus 900mc is the most powerful FDM® system available. Specifically, its accuracy, repeatability and predictability are unmatched. Additionally, the control software leverages the system's hardware advancements to deliver greater throughput and reliability.

Like all Fortus 3D Production Systems, the Fortus 900mc uses stable thermoplastics that continue to outperform nearly all competing technologies in accuracy and repeatability. Purchase only the material options you need, from a menu of 12, to build demanding functional prototypes, production parts, jigs, fixtures and factory tooling.



LEARN MORE ABOUT THE FORTUS 900MC AT STRATASYS.COM

stratasys



THE 3D PRINTING SOLUTIONS COMPANY



Fortus 900mc

At the core:

Advanced FDM technology

Fortus systems are based on Stratasys® FDM technology. FDM builds parts in production-grade thermoplastics, enabling the most durable parts.

Fortus systems use a wide range of thermoplastics with advanced mechanical properties so your parts can endure high heat, caustic chemicals, sterilization and high-impact applications.

No special facilities needed

You can install a Fortus 3D Production System just about anywhere. No special venting is required because Fortus systems produce no noxious fumes, chemicals or waste.

No special skills needed

Compared to other additive fabrication systems, Fortus 3D Production Systems are easy to operate and maintain as there are no messy powders to handle and contain. They're so simple, an operator can be trained to operate a Fortus system in less than 30 minutes.

Get your benchmark on the future of manufacturing

Fine details. Smooth surface finishes. Accuracy. Strength. The best way to see the advantages of a Fortus 3D Production System is to have your own part built on a Fortus system. Get your free part at: stratasys.com

System Specifications

SYSTEM CONFIGURATION

Build Envelope (XYZ)	914.4 x 609.6 x 914.4 mm (36 x 24 x 36 in.) Platen supports two build zones for either a small or large build sheet
Material Delivery	Two build material canisters 1508 cc (92 in. ³) Two support material canisters 1508 cc (92 in. ³) Auto changeover between canisters

MATERIAL OPTIONS

Layer Thickness:	ASA	ABSi™	ABS-M30™	ABS-M30i™	ABS-ESD7™	PC-ABS	PC-ISO™	PC	ULTEM™ 9085 resin	ULTEM 1010 resin	PPSF	FDM Nylon 12™
0.013 inch (0.330 mm)	X	X	X	X		X	X	X	X	X		X
0.013 inch (0.330 mm)	X	X	X	X	X	X	X	X	X	X	X	X
0.007 inch (0.178 mm)	X	X	X	X	X	X		X				X
Support Structure:	Soluble	Soluble	Soluble	Soluble	Soluble	Soluble	Break-away	Break-away, Soluble	Break-away	Break-away	Break-away	Soluble
Available Colors:	Ivory Black	Trans-lucent Natural Black Trans-lucent Amber Trans-lucent Red	Ivory White Black Red Blue Dark Grey	Ivory	Black	Black	Trans-lucent Natural White	White	Tan Black	Natural Tan	Tan	Black

OTHER SPECIFICATIONS

System Size and Weight	870 x 735 x 1200 mm (34.25 x 28.9 x 47.25 in.); 410 kg (902 lbs.) With Manufacturing Light Tower: 2772 x 1683 x 2281 mm (109.1 x 66.3 x 89.8 in.)
Achievable Accuracy	Parts are produced within an accuracy of +/- .0035 in. or +/- .0015 in. per in. whichever is greater (+/- .089 mm or +/- .0015 mm per mm whichever is greater)+ +Note: Accuracy is geometry-dependent. Achievable accuracy specification derived from statistical data at 95% dimensional yield. See Fortus 900mc accuracy white paper for more information.
Network Communication	10/100 base T connection. Ethernet protocol.
Operator Attendance	Limited attendance for job start and stop required.
Operating Environment¹	Maximum room temperature of 85°F (29°C). Maximum room humidity of 80%.
Power Requirements¹	230 VAC (three phase) 50/60Hz, Voltage fluctuation +/- Current 40A
Additional Requirements¹	Compressed Air Required
Regulatory Compliance¹	CE
Software	All Fortus systems include Insight™ and Control Center™ job processing and management software.
Operating System	Microsoft Windows 8.1 and Windows 8 (Pro, Enterprise), Microsoft Windows 7 (Pro, Enterprise, Ultimate), Microsoft Windows Vista (Business, Enterprise, Ultimate), Microsoft Windows Server 2008, Microsoft Windows Server 2003

¹See Fortus 900mc Site Prep Guide for detailed power and environmental specs



stratasys

E info@stratasys.com / STRATASYS.COM
ISO 9001:2008 Certified

© 2015 Stratasys. All rights reserved. Stratasys, FDM, Fortus and Finishing Touch are registered trademarks of Stratasys Inc. Fortus 250mc, Fortus 360mc, Fortus 380mc, Fortus 400mc, Fortus 450mc, Fortus 900mc, Insight, FDM Technology, Smart Supports, XTEND, SR-30, SR-100, SR-110, ABSplus, ABSi, ABS-M30, ABS-M30i, ABS-ESD7, PC-ISO, FDM Nylon 12 and TouchWorks are trademarks of Stratasys, Inc. ULTEM™ is a registered trademark of SABIC or affiliates. All other trademarks are the property of their respective owners, and Stratasys assumes no responsibility with regard to the selection, performance, or use of these non-Stratasys products. Product specifications subject to change without notice. PSSFDm_900mc_EN_0815

HEADQUARTERS

7665 Commerce Way, Eden Prairie, MN 55344
+1 888 480-3548 (US Toll Free)
+1 952 937-3000 (Intl)
+1 952 937-0070 (Fax)

2 Holtzman St., Science Park, PO Box 2496
Rehovot 76124, Israel
+972 74 745-4000
+972 74 745-5000 (Fax)