



CONNEX500

**Connex500**

The First Multi-material 3-Dimensional Printing System

Bring your models closer to your end products  
with innovative Objet inkjet-based Technology

- Closer-than-ever simulation of end products combining multiple materials
  - Multi-material parts: simultaneous jetting of different model materials
  - Mixed tray: different parts made with different materials in a single build
- Wide range of FullCure® and composite materials: photopolymer model and support materials; on-the-fly composite Digital Materials™
- Variety of build process and printing modes
- Boost your creativity with multiple materials and composite materials featuring varied material properties and tones
- Outstanding quality and accuracy
- 16-micron, high-resolution layers ensure smooth surfaces and fine details
- Superb productivity with large-size build tray of 500x400x200 mm
- Ease-of-use in an office environment

## Technical Specifications

### Layer Thickness (Z-axis)

Horizontal build layers down to 16-micron

### Tray Size (XxYxZ)

500x400x200 mm (19.7x15.7x7.9 inch)

### Net Build Size (XxYxZ)

490x390x200 mm (19.3x15.4x7.9 inch)

### Build Resolution

X-axis: 600 dpi

Y-axis: 600 dpi

Z-axis: 1600 dpi

### Printing Modes

Digital Material (DM): 30-micron (0.001 inch)

High Quality (HQ): 16-micron (0.0006 inch)

High Speed (HS): 30-micron (0.001 inch)

### Typical Accuracy

20-85um for features below 50mm

Up to 200um for full model size (for rigid materials only, depending on geometry, build parameters and model orientation)

### Supported Model Materials

- FullCure®720 General Purpose, transparent material
- Vero Family opaque materials
- DurusWhite Polypropylene-like material
- Tango Family rubber-like flexible material

### Digital Materials

Wide range of composite materials fabricated on the fly

### Support Type

- FullCure®705 Support
- Non-toxic gel-like photopolymer support easily removed by WaterJet

### Materials Cartridges:

- Four sealed 3.6 kg (7.9 lb) cartridges
- Tango family and DurusWhite also available as 1.44kg (3.17 lb) net weight in 3.6 kg casing
- Two different model materials loaded
- Front loading for quick replacement

### Power Requirements

110–240 VAC 50/60 Hz

1.5 KW single phase

### Machine Dimensions (WxDxH)

1420x1120x1130 mm

(55.9x44.1x44.5 inch)

### Machine Weight

Net 500kg (Net 1102 lb)

### Operational Environment

18°C to 22°C (64.5°F to 71.5°F)

Relative Humidity 30 – 70%

### Compatibility

Windows XP, Windows Vista

### Software

Objet Studio™ for Connex500 features:

- Easy selection of materials including Digital Materials
- Part separation into sub-assemblies
- Automatic real time support structure generation
- Suggested build orientation and speed, auto-place
- Slice on the fly
- Network version

### Input Formats

STL, OBJDF and SLC Files

### CADMatrix™ Add-in

CADMatrix add-in enables designers and engineers to seamlessly assign Objet model materials to multi-part, multi-material designs within CAD software\*, thus allowing for increased control of 3D model validation.

### Special Facility Requirements

None

### Print Heads

8 Units

### Network Communication

LAN – TCP/IP

\* CAD software: CADMatrix™ is compatible with the following: Pro/ENGINEER, SolidWorks, AutoDesk Inventor



[www.stratasys.com](http://www.stratasys.com)

[www.objet.com](http://www.objet.com)

[objet-info@stratasys.com](mailto:objet-info@stratasys.com)



Phoenix Analysis & Design Technologies  
www.PADTINC.com  
480.813.4884  
sales@padtinc.com

© 2012 Stratasys Ltd. All rights reserved. Stratasys, Stratasys logo, Objet, For a 3D World, Objet24, Objet 30 Pro, Objet Studio, Quadra, QuadraTempo, FullCure, SHR, Eden, Eden250, Eden260, Eden260V, Eden 330, Eden350, Eden350V, Eden500V, Jo Manager, CADMatrix, Connex, Objet260 Connex, Connex350, Connex500, Alaris, Alaris30, PolyLog, TangoBlack, TangoGray, TangoPlus, TangoBlackPlus, VeroBlue, VeloBlack, VeroBlackPlus, VeroClear, VeroDent, VeroGray, VeroWhite, VeroWhitePlus, Durus, Digital Materials, PolyJet, PolyJet Matrix, ABS-like and ObjetGreen are trademarks or registered trademarks of Stratasys Ltd. and/or its subsidiaries or affiliates and may be registered in certain jurisdictions. All other trademarks belong to their respective owners.

